

125 MM ROUND

(HE, HEAT-T, APFSDS-T)



HE: High-explosive round is used mainly against enemy personnel and to destroy buildings.

HEAT-T: Anti-tank round with the inner shaped charge.

HEAT-PRACTICE-T: This high-explosive round is intended for the purpose of tank crew training.

APFSDS-T: This armour-piercing cartridge consists of a fin-stabilized subprojectile and a tracer assembly attached to the rear of the fin.

SPECIFICATION

Type	HEAT-T	HE	AP-T
------	--------	----	------

COMPLETE CARTRIDGE

Weight (kg)	29,1	33	19,6
Length (mm)	1 084	1 086	1 065
Muzzle velocity (m/s)	905	850	1 800
Range of fire (m)	4 000	19 400	4 000

PROJECTILE

Weight (kg)	19.1	23.1	5.67
Length (mm)	677	618	517
Type of explosive charge	OKFOL	TNT	/
Weight of explosive charge (kg)	1.624	3.148	/
Fuze	V-15	V-429E	/

BAG-CARTRIDGE

Powder smokeless charge	15/1 TP D/A + 12/7 B/A	15/1 TP D/A + 12/7 B/A
Powder charge weight (kg)	5.89	10.8
Primer srew	GUV-7	GUV-7
Length (mm)	6.01	/



LEARN MORE: c4icommunication.com

FOR MORE INFORMATION:
contact@c4icommunication.com or +1(302)9811340